




TA-2PRT

2 POSITION REEL TRAILER



Boss Products, Inc.
602 Maple Lane
Wakarusa, Indiana 46573
Office: 574-970-0450

sales@bossproductsinc.com
www.PoleCatTrailers.com

TRAILER SPECIFICATIONS

GVWR	20,000 lbs./9,072 kg
Frame Construction	Steel Tube
Trailer Weight	3,910 lbs./1,774 kg.
Trailer Width	8 ft. 5 in.
Trailer Length	20 ft.
Tire Sizes	235/75R17.5
Wheels per Axle	2
GAWR	10,000 lbs. Tandem
Suspension	Leaf-Spring (Overslung)
Towing Electrical Plug	7-way Round Pin
Brake System	Electric with Breakaway Kit
Lighting	US DOT Regulation LED
Color	Plascoat® White Finish

REEL SPECIFICATIONS

Max Reel Width	60 in.
Max Reel Diameter	60 in. (customizable)
2.875 in. Solid Cold Rolled Steel Shaft with Crossarm & 12 in.	2
16 in. Ventilated Bronze Over	2

ACCESSORIES

Wheel Chocks	2
Clevis Hooks on Safety Chains	3/8 in.
Copper Grounding Rod	1
Lunette Ring	3 in. I.D.
Square Sidewind Hitch Jack	12,000 lbs/5,443 kg.
Square Sidewind Rear Leveling Jack	(2) 5,000 lbs with 28-11/16 in. lift
Document Holder	1
Mud Flaps	2

OPTIONS

*Bullwheel Tensioner	
Brake Pressure Gauge	1
Operator Safety Screen	1
24 in. Bullwheel (70 Durometer EPDM Lagging)	2
Bullwheel Grooves (1.5 in dia.)	5
20 in. Steel Rotor with Hydraulic Disk Brakes	2
Sliding Fairlead with 4 rollers	1
Handwheel Adjustment	2
Maximum Tension Capacity	Est. 2,400 lbs. @ 2 MPH

Tool Boxes

Stainless Steel Front—Tool Boxes	(2) 24 in. W x 14 in. H x 16 in. D
----------------------------------	------------------------------------

