



TA-U-1825



TANDEM AXLE TELESCOPING UTILITY TRAILER



Boss Products, Inc.
 602 Maple Lane
 Wakarusa, Indiana 46573
 Office: 574-970-0450
 sales@bossproductsinc.com
 www.PoleCatTrailers.com

TRAILER SPECIFICATIONS

GVWR	12,000 lbs./5,443 kg
Frame Construction	Steel Tube
Trailer Weight	3,600 lbs./1,633 kg
Trailer Width	8 ft. 1/4 in.
Trailer Length	18 ft
Extended Lenth	25 ft.
Trailer Bed Dimension	106 in L x 58 in W x 15 in. H
Telescoping Tongue Max Extensions	6 ft. 5 in (3 position)
Tire Sizes	235/80R16
Wheels per Axle	2
GAWR	6,000 lbs. Tandem
Suspension	Leaf-Spring (Underslung)
Towing Electrical Plug	7-way Round Pin
Brake System	Electric with Breakaway Kit
Lighting	US DOT Regulation LED
Color	Plascoat® White Finish
Tailgate	Fold Down

ACCESSORIES

Wheel Chocks	2
Clevis Hooks on Safety Chains	3/8 in.
Lunette Ring (with 4 mounting height locations)	2.5 in. I.D.
Square Sidewind Hitch Jack	12,000 lbs/5,443 kg. with 26 in lift
Stainless Steel Front—Tool Boxes	(2) 24 in. W x 14 in. H x 16 in. D
Document Holder	1
Tightening Bar	1
Mud Flaps	Single Wheel
Workbenches	2 (1 on each side)
Removable Utility Rack Posts with Locking Pins	1
Lashing Wenches with 5,400 lbs. Rated Straps	3

OPTIONS

Reel Carrier	1
Heavy Duty Reel Carriers with (2) Locking Reel Collars	
2.875 in. Solid Cold Rolled Steel Shaft with Brake Shaft Collar and Locking Reel Collar	
48 in. Max Reel Width	
72 in. Max Reel Diameter	
Powder Coated Plascoat® White	
Upper Parts Rack (sold individually)	4
Lower Parts Rack (sold individually)	4
Cone Holder - Side or Bottom Mount	1

Mat Rack	1
Made of 1 in. x 1 in x 0.125 in Wall Square Steel Tube	
96 in. L X 38 in. W x 4 in. H	
Powder Coated Textured Black	
Slide Out Drawers	
Slide Out Drawers 14.75 in. L X 13 in. W x 2.5 in. H	2
Table Extensions	
14 in Utility Table Extensions (for extra long pieces)	2
Brake Assembly	1
8 in. Overspun Brake with Bracket and Hardware	

